

## **CAR PREP CHECKLIST**

Driving on a race track will put stress on both car and driver. Cars should be checked to meet technical and safety standards before being brought to the track. Following is a checklist of typical requirements.

## Technical

- □ Tire wear above tread markers, correct speed rating
- $\Box$  Lug nuts present and tight<sup>1</sup>
- $\Box$  No pressed on hubcaps or beauty rings
- □ Wheels must have no sign of cracks or structural damage
- $\Box$  Over 1/2 thickness on brake pads/shoes
- $\Box$  Brake rotors must not have any cracks<sup>2</sup>
- □ Firm brake pedal
- □ Clean brake fluid, changed within 6 months, reservoir full
- □ Crack-free flexible brake lines
- □ Brake lights functional
- □ Wheel bearings tight with no play
- □ Minimum steering play
- □ Tow hook installed if available

## Safety

- □ Good 3, 4 or 5 point seat belts
- □ Good headrest
- □ Good door and window latches
- $\Box$  Open cars must have adequate roll protection<sup>4</sup>
- Glass headlights must be taped

- $\Box$  Gas cap secured
- No exposed electrical wires
- $\square$  Sound exhaust with no leaks, Intake/exhaust sound limits met<sup>3</sup>
- □ Seat bolted in tight
- □ Battery solidly mounted with positive post covered
- □ No fluid leaks (oil, fuel, water)
- $\Box$  Catch container on radiator overflow
- $\Box$  Throttle has quick, positive return
- □ Body has no loose panels, large dents, rust or large primer areas; no inappropriate signage or add-ons
- $\Box$  Sunroofs must be closed or removed
- □ At least one rear-view mirror must be present
- $\square$  Snell 2010 or newer helmet<sup>5</sup>
- □ 2.5lb fire extinguisher recommended, metal mount bracket
- $\Box$  Cotton shirt and full length pants<sup>6</sup>
- $\square$  No loose objects in car or trunk<sup>7</sup>
- □ Car must have numbers displayed on both sides, 8" tall

<sup>&</sup>lt;sup>1</sup> Typical lug nut tightness is 75-95ft-lbs, check with your wheel manufacturer for specs

<sup>&</sup>lt;sup>2</sup> Minimal hairline cracks in rotors are normal, but should not open or extend to the edge of the rotor

<sup>&</sup>lt;sup>3</sup> Sound limits are typically 103db at Thunderhill, 90db at Laguna Seca

<sup>&</sup>lt;sup>4</sup> Open cars include convertibles, purpose-built race cars without tops, roadsters, etc. Legal roll protection includes SCCA or NHRA approved bars as well as factory hoops pop-ups behind seats. All roll protection must meet broomstick test. Decorative bars are not approved.

<sup>&</sup>lt;sup>5</sup> Legal helmets include Snell SA2010, M2010. Helmets showing damage or missing a Snell sticker or 'shorty helmets' will not be approved

<sup>&</sup>lt;sup>6</sup> Faster cars should consider full fire-retardant driving suits; all drivers should strongly consider driving gloves and shoes.

<sup>&</sup>lt;sup>7</sup> Loose objects include handheld cameras (must have correct mount and safety strap), cell phones, radar detectors, tools, spare tire, jack, etc and cannot be in cab, trunk, glove box, etc